

CNTX

ADVANCED CONTRAST SENSOR

Increase process throughput with high-speed, accurate and reliable contrast differentiation. The CNTX™ combines a broad-spectrum light source, small spot size and fast response to achieve high-speed contrast differentiation of both neutral and color targets. The CNTX employs our field-proven, patented technology, for effective detection of registration marks, glossy surfaces, cap inserts, date codes and sorting of product by color in many industrial applications. The metal alloy case and glass lens provide robust construction expected in an industrial environment.

The CNTX features a 2-digit display that provides an indication of signal strength making set-up and integration quick and easy. The versatile sensor provides user set-up parameters including light source intensity adjustment, detection threshold and gain selection making the CNTX useful in a wide range of applications.

The CNTX includes both a discrete PNP/NPN output and an analog output. The discrete output is automatically set for PNP or NPN operation. The analog output signal may be used to access targets based on their reflectance characteristics.

CNTX



EMX Industries, Inc.

4564 Johnston Parkway, Cleveland, Ohio 44128

P. 800 426 9912 F. 216 518 9884

Sales Inquiries: salesupport@emxinc.com **Technical Support:** technical@emxinc.com

www.emxinc.com



Applications

- Sort products by color
- Detect registration marks
- Confirm presence of date codes
- Detection of glossy surfaces
- Detects cap inserts

Design & Features

- 0.5mm or 3.0mm spot size
- 25uS response time
- Display range 00-50
- Broad spectrum white LED
- Adjustable LED intensity
- Two gain settings
- Programmable discrete output
- Threshold adjustment
- Analog output

Ordering Information



CNIX-30-0
Advanced Contrast Sensor
3.0mm light spot



CNIX-05-0
Advanced Contrast Sensor
0.5mm light spot

Accessories



UVX-300B
Bracket



UVX-300C
Cable 5P, 5M, M12, F

Functions

NORMAL OPERATING MODE
SENSITIVITY
THRESHOLD
LED INTENSITY
HYSTERESIS LEVEL
DISCRETE OUTPUT
OUTPUT PULSE STRETCH
SECURITY
TEACH MODE

Displays relative reflection intensity
 X1 and X10
 Set detection level
 Set LED, LO, MED, HI
 Set undetect level 1-9 steps below threshold
 Set normally open or normally closed
 Set minimum output period 10...90mS
 Lock/unlock pushbutton controls
 Auto-set detection threshold

Specifications

| | | | |
|---|---|--------------------------|----------------------------------|
| White light source | Broad spectrum LED, min. 100,000 hours 28mm | Indicators | LED |
| Sensing distance | 0.5mm or 3.0mm dia. | 7-Segment display | Power |
| Spot size | +/- 3mm | Green LED | Detect |
| Depth of field | 25uS | Red LED | Program |
| Response time | 40kHz | Yellow LED | |
| Switching Frequency | 3 levels | Connector M12 | |
| LED intensity | 00 to 50 | Pin 1 | Power to 24VDC |
| Relative intensity display range | 1X, 10X | Pin 2 | Discrete output PNP/NPN NO/NC |
| Sensitivity | Two 7 segment digits | Pin 3 | Ground |
| Signal level | Two 7 segment digits | Pin 4 | Analog output 0 to 5V DC |
| Detection threshold | Auto-Detect NPN / PNP | Pin 5 | Remote LOCK/ UNLOCK input |
| Digital Output | NO/NC selectable | | |
| Output Function | LOCK/UNLOCK keypad | | |
| Security | Green LED | | |
| Power indicator | Red LED | | |
| Detect indicator | Yellow LED | | |
| Programming indicator | EEPROM non-volatile memory | | |
| Data retention | 2.0" (51mm) x 2.4" (61mm) x 1.0" (25mm) | | |
| Dimensions | 0.21 lbs. (95g) | | |
| Weight | 10-24 VDC | | |
| Supply Voltage | 60 mA | | |
| Operating Current | Discrete output | | |
| Short Circuit Protection | Supply voltage | | |
| Overload / Reverse Polarity Protection | -20°C...55°C | | |
| Operating temperature | -20°C...70°C | | |
| Storage temperature | Metal alloy | | |
| Housing | IP65 NOT FOR PRESSURE WASH DOWN | | |
| Mechanical Protection | | | |

WARRANTY EMX INC. the product described herein for a period of 2 years under normal use and service from the date of manufacture. The product will be free from defects in material and workmanship. This warranty does not cover ordinary wear and tear, abuse, misuse, overloading, altered products, or damage caused by the purchaser from incorrect connections, or lightning damage. There is no warranty of merchantability. There are no warranties expressed, implied or any affirmation of fact or representation which extend beyond the description set forth herein. EMX Inc. sole responsibility and liability, and purchaser's exclusive remedy shall be limited to the repair or replacement at EMX's option of a part or parts not so conforming to the warranty. In no event shall EMX Inc. be liable for damages of any nature, including incidental or consequential damages, including but, not limited to any damages resulting from non-conformity defect in material or workmanship.